

CSA-W



CASSETTE TYPE FAN COIL



www.fujiair.com

SPECIFICATION

Description		CSA-09W	CSA-12W	CSA-15W	CSA-18W	CSA-25W	CSA-30W	CSA-36W	CSA-42W	
Cooling Capacity	Btu/h	9,212	12,283	15,354	18,425	24,566	30,708	36,850	42,991	
	Watt	2,700	3,600	4,500	5,400	7,200	9,000	10,800	12,600	
Heating Capacity	Btu/h	13,819	18,425	23,031	27,637	36,167	46,062	55,274	64,828	
	Watt	4,050	5,400	6,750	8,100	10,600	13,500	16,200	19,000	
Air Flow Volume	CFM	300	400	500	600	800	1000	1200	1400	
	CMH	510	680	850	1,020	1360	1,700	2,040	2,380	
Noise Level	dB (A)	42	42	45	48	48	50	50	50	
Fan	Type	Turbo Fan								
Fan Motor	Power Supply	V/Ph/Hz	220-240 / 1 / 50/60							
	Input	Watt	50	65	70	110	130	150	185	210
Connection	Water in/out	Inch	3/4" ϕ Copper Tube/3/4" ϕ Copper Tube							
	Drain	Inch	3/4" ϕ uPVC pipe							
Water flow rate	GPM	2.3	2.7	3.8	4.3	5.4	7.0	8.4	9.7	
	L / M	8.7	10.3	14.3	16.3	20.3	26.3	32.0	36.7	
Thermostat	Type	Wireless Remote Control								
Pressure drop	Ft. of WG.	8.4	9.4	9.4	10.8	10.8	11.8	11.8	14.1	
	kPa	25	28	28	32	32	35	35	42	
Hanged Brackets	No.	4	4	4	4	4	4	4	4	
	Rod Hole Size	mm.	8	8	8	8	8	8	8	
Air Filter	Type	Washable, honey-comb net synthetic type								
Dimension	Cassette : L x W x D	mm.	570 x 570 x 250			850 x 850x 240		850 x 850 x 282		
	Air Panel : L x W x D	mm	650 x 650x30			950 x 950x45				
Net Weight	Cassette	kg	18.5	23	23	28	28	31	31	31
	Air Panel	kg	2.2	2.2	2.2	7	7	7	7	7

Remark:

1. Standard Cooling Condition: Air inlet Temp. DB 27°C, WB 19.5°C, Chiller water inlet/out temperature 7°C/12°C;
2. Standard Heating Condition: Air inlet Temp. DB 21°C, hot water inlet Temp. 60°C.
3. FUJIAIR reserves the right to change the specification without prior notice.